

|                                          |                 |                      |                                                                                                                                                                                                                                                                                                             |
|------------------------------------------|-----------------|----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <div>Gerflor®<br/>theflooringgroup</div> |                 | Mipolam Elegance EL5 |                                                                                                                                                                                                                                                                                                             |
| DESCRIPTION                              |                 |                      |                                                                                                                                                                                                                                                                                                             |
| Total thickness                          | EN 428          | mm                   | 2.00                                                                                                                                                                                                                                                                                                        |
| Weight                                   | EN 430          | g/sq.m               | 3060                                                                                                                                                                                                                                                                                                        |
| Width of sheet                           | EN 426          | cm                   | 200                                                                                                                                                                                                                                                                                                         |
| Length of sheet                          | EN 426          | lm                   | 20                                                                                                                                                                                                                                                                                                          |
| Coverage / roll                          | -               | sq.m                 | 40                                                                                                                                                                                                                                                                                                          |
| CLASSIFICATION                           |                 |                      |                                                                                                                                                                                                                                                                                                             |
| Standard / Product specification         |                 | -                    | EN 649                                                                                                                                                                                                                                                                                                      |
| European classification                  | EN 685          | class                | 34 - 43                                                                                                                                                                                                                                                                                                     |
| Fire rating                              | EN 13501-1      | class                | B <sub>fl</sub> -s1                                                                                                                                                                                                                                                                                         |
| Electrical resistance                    | EN 1081*        | Ohm                  | 5x10 <sup>4</sup> ≤ Rt ≤ 10 <sup>6</sup>                                                                                                                                                                                                                                                                    |
|                                          | IEC 61340-5-1   | Ohm                  | Rt ≤ 10 <sup>6</sup>                                                                                                                                                                                                                                                                                        |
|                                          | ANSI / ESD-S7.1 | Ohm                  | 2.5x10 <sup>4</sup> ≤ Rt ≤ 10 <sup>6</sup>                                                                                                                                                                                                                                                                  |
| Static electrical propensity             | EN 1815         | kV                   | < 2                                                                                                                                                                                                                                                                                                         |
|                                          | IEC 61340-4-5   | V                    | ≤ 100**                                                                                                                                                                                                                                                                                                     |
| Slip resistance                          | DIN 51130       | class                | R9                                                                                                                                                                                                                                                                                                          |
| PERFORMANCE                              |                 |                      |                                                                                                                                                                                                                                                                                                             |
| Wear resistance                          | EN 660.2        | mm <sup>3</sup>      | ≤ 4.0                                                                                                                                                                                                                                                                                                       |
| Wear group                               | EN 649          | -                    | P                                                                                                                                                                                                                                                                                                           |
| Type Binder content                      | ISO 10581       | type                 | I                                                                                                                                                                                                                                                                                                           |
| Dimensional stability                    | EN 434          | %                    | ≤ 0,40                                                                                                                                                                                                                                                                                                      |
| Residual indentation                     | EN 433          | mm                   | ~ 0,02                                                                                                                                                                                                                                                                                                      |
| Castor chair test (type W)               | EN 425          | -                    | OK                                                                                                                                                                                                                                                                                                          |
| Thermal conductivity                     | EN 12 524       | W/(m.K)              | 0.25                                                                                                                                                                                                                                                                                                        |
| Colour fastness                          | EN 20 105 - B02 | degree               | ≥ 6                                                                                                                                                                                                                                                                                                         |
| Surface treatment                        | -               | -                    | Evercare™                                                                                                                                                                                                                                                                                                   |
| Chemical products resistance             | EN 423          | -                    | OK                                                                                                                                                                                                                                                                                                          |
| ENVIRONMENT / INDOOR AIR QUALITY         |                 |                      |                                                                                                                                                                                                                                                                                                             |
| TVOC after 28 days                       | ISO 16000-6     | µg/ m <sup>3</sup>   | < 10                                                                                                                                                                                                                                                                                                        |
| Certification                            | -               | -                    | Floorscore®                                                                                                                                                                                                                                                                                                 |
| MARQUAGE CE                              |                 |                      |                                                                                                                                                                                                                                                                                                             |
| <div>CE</div>                            | EN 14041        | -                    | <div><div></div><div></div><div></div></div> |
|                                          |                 | -                    | <div></div>                                                                                                                                                                                                            |

\* Measured glued as defined by Gerflor installation guidelines

\*\* Measured with ESD shoes (ABEBA and Uvex)