

 6 Ø 8 SPONKA V RASTRU 500 X 500 MM

8) 2850 ø 8 L=355mm

9) 2850 ø 8 L=355mm

10) 10 ø 10 L=2580mm

11) 10 ø 10 L=3300mm

12) 11 ø 10 L=1055mm

13) 11 ø 10 L=1395mm

14) 96 ø 10 L=1390mm

15) 96 ø 10 L=2215mm

16) 96 ø 10 L=2170mm

17) 11 ø 10 L=2440mm

Figure 1 shows ten examples of structural members defined using the proposed notation. Each example is labeled with a circled number and a text description of the member's geometry and properties.

- 1. A vertical member with length 100 and diameter 46. Notation: $\textcircled{46} \text{ } 100 \text{ } 10 \text{ L}=1925\text{mm}$
- 2. A vertical member with length 100 and diameter 35. Notation: $\textcircled{35} \text{ } 100 \text{ L}=2710\text{mm}$
- 3. A horizontal member with length 100 and diameter 46. Notation: $\textcircled{46} \text{ } 100 \text{ L}=1925\text{mm}$
- 4. A vertical member with length 100 and diameter 46. Notation: $\textcircled{46} \text{ } 100 \text{ L}=1925\text{mm}$
- 5. A vertical member with length 100 and diameter 46. Notation: $\textcircled{46} \text{ } 100 \text{ L}=1925\text{mm}$
- 6. A vertical member with length 100 and diameter 46. Notation: $\textcircled{46} \text{ } 100 \text{ L}=1925\text{mm}$
- 7. A vertical member with length 100 and diameter 46. Notation: $\textcircled{46} \text{ } 100 \text{ L}=1925\text{mm}$
- 8. A vertical member with length 100 and diameter 46. Notation: $\textcircled{46} \text{ } 100 \text{ L}=1925\text{mm}$
- 9. A vertical member with length 100 and diameter 46. Notation: $\textcircled{46} \text{ } 100 \text{ L}=1925\text{mm}$
- 10. A vertical member with length 100 and diameter 46. Notation: $\textcircled{46} \text{ } 100 \text{ L}=1925\text{mm}$

(42) 101 ø 10 L=1170m

A diagram of a long, narrow rectangular structure, possibly a conveyor belt or a track. It consists of two parallel horizontal lines. Between these lines, there are two rows of small circles, one row near the top and one row near the bottom. A diagonal line segment is drawn across the upper part of the rectangle, starting from the top edge and extending towards the center.

[illegible]

V MÍSTĚ OTVORŮ VÝZTUŽ PROSTŘEHNOUT ČI POSADNOUT

[illegible]

Revize	Výpiscová	Popis revize	Datum	
			Hlavní idenční projekt: ING. LUDĚK TOMEK Vedoucí projektant zakázky: ING. JAN KOČMÁNEK	
Investor  FAKULTNÍ NEMOCNICE OLMOUC			Autorizace:	
Projedná:	STATIKA		Statika Balčáček s.r.o. Zaměstnavatel: Z. 779 03 Olomouc tel.: +420 733 671 110 E-mail: l.tatarkan@seznam.cz	
Odpovědný projektant:	Výpiscová:	Kontroloval:		
ING. FRANTIŠEK BALČÁČEK	ING. FRANTIŠEK BALČÁČEK	ING. FRANTIŠEK BALČÁČEK		
Ako:	FAKULTNÍ NEMOCNICE OLMOUC STAVĚNÍ ÚPRAVY OBJEKTU "D" ÚNIKOVÉ CESTY			Zakázkové číslo: 12 - 2020 Datum: 12 - 2020 Stupeň: DPS
Ognet:	BUDOVA A - NÁSTAVBA	SO 01	Formát:	Paré:
Osah:	VÝKRES VÝZTUŽE STĚN			Mřížko: Číslo výkresu:
				D.1.01.2-106

VÝZTUŽ POSUNOUT MIMO PROSTUP[®]

D.1.01.2-106